Tri-Creaser Fast-Fit Advance Female Upgrade

upgrade to be used with Fast-Fit with 59.4mm outer diameter

Stock Code: FF-GU/35-DSF Shaft Size: 35mm Exit Shaft

Outer Diameter: 59.4mm

SETTINGS



Optional Items

If fibre-cracking is not a problem these deep and penetrating nylon ribs are ideal for laminated and section work:

FF-PC-GU/35-R Red light crease
FF-PC-GU/35-B Blue medium crease
FF-PC-GU/35-Y Yellow heavy crease

White Very Narrow Female Receiver Ring (FF-DSF/GU-35-NY-W):

used to crease material weights between 60-200gsm

Additional Information

Compatible with:

SM 50/2 FA 50 SM 54/4 FA 74 SM 74/4

5111 7 17 1

How it works...

This attachment is designed to be used with your existing Fast-Fit Male Creasing Rib Holder (see picture below for illustration of them working together):



Contents of Package

1x Female Receiver Holder Component (F): holds receiver rings in which material is pressed

1x Red Female Receiver Ring (FF-DSF/GU-35-NY-R): used to crease material weight between 85-150gsm

1x Blue Female Receiver Ring (FF-DSF/GU-35-NY-B): used to crease material weight between 150-250gsm

1x Yellow Female Receiver Ring (FF-DSF/GU-35-NY-Y): used to crease material weight between 250-350gsm

1x Orange Split Gripper Crease (M-114B-XTRA): used to crease material weight between 85-150gsm

1x Blue Split Gripper Crease (M-113B-XTRA): used to crease material weight between 150-250gsm

1x Yellow Split Gripper Crease (M-104B-XTRA): used to crease material weight between 250-350gsm

1x Extraction Tool:

used to remove the inserts from Male Component



Tech 496