

# Tri-Creaser Fast-Fit Advance System

## Fast-Fit Tri-Creaser with Advance Female to fit 40mm exit shaft

Stock Code: **FF-MF/40-FP-DSF-01-B**

Shaft Size: **40mm Exit Shaft**

Outer Diameter: **58mm**

### SETTINGS



### Additional Information

#### How it works...

Instead of the traditional metal receiving grooves in the previous Tri-Creaser Fast-Fit, the nylon Female Receiver Rings are fitted with a special profile designed to apply a double-reverse crease either side of the male creasing rib.



### Optional Items

If fibre-cracking is not a problem these deep and penetrating nylon ribs are ideal for laminated and section work:

<b>FF-PC/35-R</b>	<b>Red</b> light crease
<b>FF-PC/35-B</b>	<b>Blue</b> medium crease
<b>FF-PC/35-Y</b>	<b>Yellow</b> heavy crease
<b>FF-PC/35-BLK</b>	<b>Black</b> extra heavy crease

**White Very Narrow Female Receiver Ring (FF-DSF/35-NY-W):**  
used to crease material weights between 60-200gsm

## Contents of Package

**1x Male Creasing Rib Holder Component (M):**  
contains the split gripper crease ribs

**1x Orange Split Gripper Crease (M-163B):**  
used to crease material weight between 85-150gsm

**1x Blue Split Gripper Crease (M-162B):**  
used to crease material weight between 150-250gsm

**1x Yellow Split Gripper Crease (M-161B):**  
used to crease material weight between 250-350gsm

**1x Extraction Tool:**  
used to remove the inserts from Male Component

**1x Black Gripper Band (M-15):**  
used to support and feed sheet through the device

**1x Female Receiver Holder Component (F):**  
holds receiver rings in which material is pressed

**1x Red Female Receiver Ring (FF-DSF/35-NY-R):**  
used to crease material weights between 85-150gsm

**1x Blue Female Receiver Ring (FF-DSF/35-NY-B):**  
used to crease material weights between 150-250gsm

**1x Yellow Receiver Ring (FF-DSF/35-NY-Y):**  
used to crease material weights between 250-350gsm



Tech 386 / Tech 492