Tri-Creaser Fast-Fit Advance System

Fast-Fit Tri-Creaser with Advance Female to fit 29.62mm exit shaft

Stock Code: FF-DM-DSF-01-B Shaft Size: 29.62mm Exit Shaft

Outer Diameter: 2"/50.8mm

SETTINGS



Additional Information

How it works...

Instead of the traditional metal receiving grooves in the previous Tri-Creaser Fast-Fit, the nylon Female Receiver Rings are fitted with a special profile designed to apply a double-reverse crease either side of the male creasing rib.



Optional Items

If fibre cracking is not a problem these deep and penetrating nylon ribs are ideal for laminated and section work:

Yellow heavy crease FF-PC/DM-Y FF-PC/DM-B Blue medium crease FF-PC/DM-R **Red** light crease

Black Extra Wide Female Receiver Ring (RS-NY/FE): used to crease material weights 300gsm and above

Contents of Package

1x Male Creasing Rib Holder Component (M):

contains the split gripper crease ribs

1x Orange Split Gripper Crease (M-124BSX): used to crease material weight between 85-150gsm

1x Blue Split Gripper Crease (M-123BSX):

used to crease material weight between 150-250gsm

1x Yellow Split Gripper Crease (M-122BSX):

used to crease material weight between 250-350gsm

1x Extraction Tool:

used to remove the inserts from Male Component

1x Black Gripper Band (M-51):

used to support and feed sheet through the device

1x Female Receiver Holder Component (F): holds receiver rings in which material is pressed

1x Red Female Receiver Ring (RS-NY/FE-R):

used to crease material weights between 85-150gsm

1x Blue Female Receiver Ring (RS-NY/FE-B): used to crease material weights between 150-250gsm

1x Yellow Female Receiver Ring (RS-NY/FE-Y):

used to crease material weights between 250-350gsm



Tech 467M (Male) / Tech 525 (Female)