Outer Diameter: 2"/50.8mm

Tri-Creaser Fast-Fit Advance Female Upgrade

Upgrade to be used on Fast Fit on 29.62mm exit shaft

Stock Code: FF-DM-DSF Shaft Size: 29.62mm Exit Shaft

SETTINGS



Additional Information

How it works...

Instead of the traditional metal receiving grooves in the previous Tri-Creaser Fast-Fit, the nylon Female Receiver Rings are fitted with a special profile designed to apply a double-reverse crease either side of the male creasing rib.



Optional Items

If fibre cracking is not a problem these deep and penetrating nylon ribs are ideal for laminated and section work:

FF-PC/DM-Y
FF-PC/DM-B
FF-PC/DM-R
FF-PC/DM-R
FF-PC/DM-R
FF-PC/DM-R
FF-PC/DM-R

Black Extra Wide Female Receiver Ring (RS-NY/FE): used to crease material weights 300gsm and above

Contents of Package

1x Female Receiver Holder Component (F): holds receiver rings in which material is pressed

1x Red Female Receiver Ring (RS-NY/FE-R): used to crease material weights between 85-150gsm

1x Blue Female Receiver Ring (RS-NY/FE-B): used to crease material weights between 150-250gsm

1x Yellow Female Receiver Ring (RS-NY/FE-Y): used to crease material weights between 250-350gsm

1x Orange Split Gripper Crease (M-124BSX):

used to crease material weight between 85-150gsm $\,$

1x Blue Split Gripper Crease (M-123BSX):

used to crease material weight between 150-250gsm

1x Yellow Split Gripper Crease (M-122BSX):

used to crease material weight between 250-350gsm

1x Extraction Tool:

used to remove the inserts from Male Component



Tech 525 (Female)